

COLONIAL POST

ANCHORING INSTRUCTIONS

1. Obtain proper anchor bolts, nuts, washers and template from manufacturer.
2. Pour a 36" concrete footer, making sure to adjust depth to your local frost level and leave access for the inlet supply. (footer should be a minimum of 3" larger in diameter than the provided template)
3. Place anchor bolts with threaded side up half way into the concrete. Align anchor bolts centered side to side and front to back in the four arms of the star shape template(see diagram). Push anchor bolts into the concrete leaving approximately 2" of the threaded bolt above the concrete surface.
4. After situating to desired position, let concrete dry thoroughly.
5. If using a 3.5"OD or a 4"OD post, secure the reducing collar at the top of the post. (If not already installed, for 3.5" or 4" fluted, slide the reducing collar down in the post and secure by using the (3)set screws around the top of the post. For 4" OD, slide the collar over the post and secure by using the (3)set screws in the collar)
6. Once the concrete has thoroughly hardened, place one nut on each anchor bolt and tighten it down as far as it will go then place one washer over each of the anchor bolts.
7. Remove the access door and place the post over the anchor bolts. Place one washer on each bolt and secure by tightening one nut on each bolt. Plum the post by loosening and tightening the anchor bolts one at a time.
8. For Gas: With the coiled end at the top, slide the gas feed line down through the post. With the access door off, connect the copper feed line to the main supply and replace the access door.
9. For Electric: Feed the main line in through the inlet supply and up through to the top of the post.
10. Follow the installation instructions packed with your lamp.

